**Brand:** Clickone

Model: Clickone V2

Name: Wireless presentation system





## **Key Features:**

### **Hardware Architecture:**

- \* Rockchip multimedia chip, A7 1.4GHz quad-core CPU;
- \* Built-in dedicated hardware video codec processor, supporting 1 channel of 4K decoding or 2 channels of 1080P decoding + 1 channel of 1080P encoding simultaneously.
- \* Operating system: LINUX, with high stability, capable of running 24/7.

### **Supported Operating Systems:**

- \* Windows 7/10/11 (32-bit and 64-bit)
- \* MAC OS X 10.10 and above
- \* Wireless screen sharing for smartphones/tablets: Supports AirPlay, recommended iOS9 and above.
- \* Supports Android and HarmonyOS APP screen sharing (Android 5.0 and above).

### Hardware Interfaces:

- \*1 x HDMI 2.0 output interface;
- \* 1 x 3.5mm audio interface;

- \* 1 x USB2.0 interface;
- \* 1 x TYPEC USB2.0 interface;
- \* 1 x 5V/1A power interface;
- \* 1 x power switch.

### **HDMI Output Resolution:**

\* Supported resolution: 3840x2160P60、1920x1200P60、1920x1080P60、1280x720P60、1024x768P60

Formats: H.265, H.264

Codec Capability: Maximum 4K30 support

## **Screen Sharing Features:**

- \* Sources simultaneously on screen: 2
- \* Supports three types of transmitters: USB transmitter (1080P encoding), HDMI transmitter (1080P/4K encoding), and TYPE-C transmitter (1080P/4K encoding).
- \* Supports pure software screen sharing for Windows through WIN Sender application software.
- \* Supports simultaneous display of multiple mobile devices and mixed display.

#### Wireless Transmission:

- \* Supports dual WiFi: The hotspot AP is 5G/2.4G module with external dual antennas.
- \* The wireless network card is 5G/ 2.4G module with external dual antennas.
- \* Supports wireless bridging and wired bridging.

#### **Additional Features:**

- \* Supports screen sharing code functionality, automatic full-screen display
- \* Supports extended desktop screen sharing.
- \* Wireless transmission distance: 50 meter
- \* Transmission delay: Less than 150ms

# **Environmental Requirements:**

- \* Operating temperature: +5°C ~ +40°C
- \* Storage temperature: -20°C ~ +60°C
- \* Humidity range: 0 ~ 90% relative humidity, non-condensing